de Havilland Dominie/Rapide in Military Service



For the best results these decals should be applied to a gloss surface such as provided by either Xtracolor or Xtracrylix paints. Cut out the decal required and soak in warm water until the decal is released from the backing paper. Wet the area to be decaled with MICRO SET which will help to eliminate air trapped under the decal and position the decal.

After 5 or 10 minutes wet the decal with MICRO SOL which will soften the decal and ensure that it settles down over any surface detail. Allow the decal to dry for at least 12 hours. During this time some wrinkling of the decal may occur, this is normal. Do not touch the decal at this time.

Carefully check for small air bubbles and if there are any prick with a needle and apply a drop of MICRO SOL. After all air bubbles have been eliminated and the decals are dry wash the entire model with water to remove any excess decal adhesive.

When completely dry the whole model should be sprayed with a coat of Xtracolor or Xtracrylix Flat, Satin or Gloss varnish depending on the finish required.

Store in a cool dry place, avoid sunlight, dampness or extremes of temperature and/or humidity.




www.hannants.co.uk


Harbour Road, Oulton Broad, Lowestoft, Suffolk, NR32 3LZ

Phone +44 1502 517444

Fax +44 1502 500521

sales@hannants.co.uk





Xtracolor Paints

X002 BS381C:450 Dark Earth

X009 Middle Stone

X012 BS381C:642 Night Black

X018 BS381C:285 NATO Green

X026 Azure Blue

X029 BS381C:369 Light Stone

X105 FS13531 Sand

X112 ANA 613 Olive Drab

X133 FS16270 Neutral Gray

X149 FS15622 Pale Blue

X260 RAL 7035 Lichtgrau

X405 White X501 Silver

Paints:

The colours used on these aircraft can be found in the Xtracolor (prefix number with X) and Xtracrylix (prefix number with XA1) range of paints.

Xtracrylix Paints

XA1002 BS381C:450 Dark Earth XA1009 Middle Stone XA1012 BS381C:642 Night Black XA1026 Azure Blue XA1112 ANA 613 Olive Drab XA1133 FS16270 Neutral Gray

